

# CCTV Υβριδικό + Δικτυακό DVR

## 5MP XVR + IP CAM



**RMH**  
Competitive  
x28






- μ μ 5MP (2592 x 1920) CCTV
- TVI, AHD, CVI μ IP μ
- OSD μ μ μ (UTC)
- IP μ μ Onvif (V2.4)
- , μ
- μ ,

**iCATCH**



[www.icatchinc.com](http://www.icatchinc.com)

# RMH Competitive x28

Μοντέλο		RMH-0428EU-1	RMH-0428MU-4	RMH-0828EU-1	RMH-0828MU-4	RMH-1628EU-4	RMH-1628MU-4
							
μ		4CH AHD, TVI, CVI, IPC		8CH AHD, TVI, CVI, IPC		16CH AHD, TVI, CVI, IPC	
μ		1		4		1	
		TVI/AHD/CVI: 4MP @ 15 fps, 3MP @ 18 fps, 1080P @ 30/25 fps, 720P @ 30/25 fps, 960H / D1 @ 30/25fps					
Ήχος	Bandwidth (1 άτομο με απομακρυσμένη σύνδεση)	M . 40Mbps (M . : 6 Mbps + 1 Mbps )		M . 50Mbps (M . : 6 Mbps + 1 Mbps )		M . 115Mbps (M . : 6 Mbps + 1 Mbps )	
	Single Live & Playback channel (without Analog camera input)	M . 4MP-3MP~1080P@30/25 fps (ONVIF 2.4)		M . 4MP-3MP~1080P@30/25 fps (ONVIF 2.4)		M . 4MP-3MP~1080P@30/25 fps (ONVIF 2.4)	
	Multiple Live & Playback channels (without Analog camera input)	VGA@ 4 x 30/25 fps		VGA@ 8 x 30/25 fps		VGA@ 16 x 30/25 fps	
Έξοδος		1 HDMI μ 1 VGA (Max. 1920x1080) 1 Main BNC		1 HDMI μ 1 VGA (Max. 1920x1080) 1 Main BNC		1 HDMI (M . 3840 x 2160)μ 1 VGA (M . 1920x1080) 1 Main BNC	
μ		4		4		4	
		Audio Codec : G726 , G711 u/a IMA_ADPCM					
Έξοδος		1		1		1	
Λογισμικό		μ μ Linux					
SATA		M . 1 x SATA (HDD x 1)		M . 2 x SATA (HDD x 2)		M . 2 x SATA (HDD x 2)	
HDD		N/A		N/A		N/A	
/		N/A		N/A		N/A	
USB Ports		RS-485 USB2.0 x2					
( mm )		250mm(W)X 215mm(D) X 45mm(H)		250mm(W)X 215mm(D) X 45mm(H)		250mm(W)X 215mm(D) X 45mm(H)	
		12V 2A , 24W		12V 2A , 24W		12V 2A , 36W	
μ		1,4, SEQ.		1,4, 8, SEQ.		1, 4, 9, 13, 16, SEQ.	
μ		: 1 ~ 99 sec					
		Zoom, Auto SEQ. H.264 High Profile					
μ		2592 x 1944, 2592 x 1520, 2018 x 1524, 1920 x 1080, 1280 x 720; 944 x 480, 704 x 480, 352 x 240 (NTSC) / 944 x 576, 704 x 576, 352 x 288 (PAL)					
( )		640 x 360 / 352 x 240, 176 x 120 ( NTSC) / 352 x 288, 176 x 144 (PAL)					
		10~100 μ					
		μ μ / ,					
- μ		TVI/AHD/CVI : 4MP @ 15/12 fps, 3MP @ 15/12 fps, 1080P @ 30/25 fps, 720P @ 30/25 fps, 960H / D1 @ 30/25 fps					
- μ		1 ~ 5					
		1 ~ 100					
Zoom		μ μ / , * (x2 ~ x5)					
		10/100 Ethernet					
		TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS					
μ		Windows 7 , 8, 8.1, 10 Mac OS X					
Remote Software		SoCatch, IE Browser, iCMS Pro					
μ		1 + 10					
		Windows Phone 7.8, 8.1, 10 iPhone, iPad, Android					
		USB or SATA					
		YES					
		, USB flash, SATA DVD..					
μ		: 100 : μμ					
		10000 ( μ μ , μ HDD, μ HDD)					
OSD & μ DVR	μ						
	USB	NAI					
		(USB , LCD , EETI Chipset μ )					
	μ	- USB , iWatchDVR					
μ	μ RS485 ( Pelco P, Pelco D, Samsung, LG, LiLin )						
	0°C ~ +55°C (32°F ~ 131°F)						
	10%~80%						

All specifications are subject to change without notice.