

GS320

Piezo glassbreak detector with relay output 2 m

High Performance

The glassbreak detector GS320 with relay output is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS320 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard. They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



Standard Features

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

GS320

Piezo glassbreak detector with relay output 2 m

Specifications

General	
Technology	Piezo
Range	2 m radius
Glass types	Plate
Tamper switch	No
Wired/wireless	
Wired-Wireless	Wired
Electrical	
Power supply value	9 to 18 VDC
Current consumption	4 mA @ 6 VDC 5mA @ 12 VDC
Physical	
Physical dimensions	37 x 19 x 12 mm
Net weight	50 g
Colour	White
Mount type	Surface Mount
Environmental	
Operating temperature	-25 to +70°C
IP-rating	IP67

Ordering Information

Part No.	Description
GS320	Piezo glassbreak detector with relay output 2 m