

## TX-2213-03-1

Wireless PIR 12m 868AM Gen2



## **Details**

- Proven mirror optics inside to get a dense coverage pattern
- Selectable coverage pattern using mirror masks
- Full under crawl detection
- "5D" signal processing for false alarm immunity
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 5-years battery life with 1 battery
- Holding several security approvals

## TX-2213-03-1

Wireless PIR 12m 868AM Gen2

## **Technical Specifications**

					i
( ¬	Д	n	Д	ra	ı

General			
Technology	PIR		
Anti masking	No		
Pet immune	No		
Camera	No		
Detector start-up time	1 min		
Pry-off tamper kit	On board		
Detection			
Detection range selection	6 or 12m		
Undercrawl protection	Yes		
Coverage (field of view)	86°		
No. of curtains	9		
Target speed range	0.3 m/s to 3 m/s		
Wired/wireless			
Wired-Wireless	Wireless		
Wireless frequency	868 MHz AM		
Electrical			
Current consumption	22 μA (avg.), 50 mA (max.)		
Batteries	1 x CR123 (3.0 V, 1300 mAh lithium)		
Battery lifetime	5 years		
Physical			
Mounting height	1.8 to 3 m		
Physical dimensions	130 x 69 x 53 mm		
Net weight	146 g		
Environmental			
Operating temperature	-10° tot +55° C		
Relative humidity	95% max. noncondensing		
Environment	Indoor		
IP-rating	IP30 IK02		
Standards & regulation	on		
Certification	INCERT		
EN50131 Grade	Grade 2		

