

Double PIR Detectors for Windows and Doors

- Selectable 1 or 2 pulse count
- AND/OR selectable operating function
- Alarm LED indicator selectable ON/OFF
- Tamper switch
- Fresnel lenses
- Automatic temperature compensation
- Low current version for wireless systems (with optional wireless transmitter)
- · Antimasking and Dual-tech antimasking versions available



DESCRIPTION

Designed to be mounted on the top side of windows and doors to be protected, HE-100X series offers two PIR sensors with narrow curtain coverage.

A Dual-tech antimasking version with microwave antenna is available in both hardwired and battery operated models.











DETECTION RANGE

PRONT VIEW SIDE VIEW MICROWARE 2 2 1.2 1.0.5

DIMENSIONS (mm)





SPECIFICATIONS

Model	HE-100X	HE-101X	HE-100XAM	HE101XAM	HE-100XDAM	HE101XDAM	HE-110X	HE-111X	HE-110XAM	HE111XAM	HE-110XDAM	HE111XDAM
Power input	11.5 ~ 15.5VDC						from 3.6VDC to 6VDC					
Current drain stand-by	10 mA					30μΑ				30μΑ		
alarm	3 mA				800μΑ				20mA			
Frequency microware	-			24 GHz		-			24 GHz			
Range microware	_			4	m			_		4 m		
Detection zones	4											
Alarm output	N.C. relay max 100 mA@60VDC					open collector 100mA@50VDC						
Tamper/Anti Mask	N.C.											
Alarm LED Indicator	ON/OFF selectable											
Operating temperature	-20°C ~ +50°C											
Operating humidity	85% max											
IP rating	IP55											
Colour	White	Brown	White	Brown	White	Brown	White	Brown	White	Brown	White	Brown



	Hardwired model	Low current models (no built-in transmitter)			
CODE	MODEL	CODE	MODEL		
HE100X	HE-100X	HE110X	HE-110X		
HE101X	HE-101X	HE111X	HE-111X		
HE100XAM	HE-100XAM	HE110XAM	HE-110XAM		
HE101XAM	HE-101XAM	HE111XAM	HE-111XAM		
HE100XDAM	HE-100XDAM	HE110XDAM	HE-110XDAM		
HE101XDAM	HE-101XDAM	HE111XDAM	HE-111XDAM		



HESA S.p.A.