

RS2-WE



Defence for doors, windows, shutters & gates

Perimeter protection that rolls with
the function

A roller shutter and magnetic contact that is ready to protect any property's perimeter! Connect it to doors, windows and gates and the RS2-WE is ready and waiting to raise an alarm if any are opened without authorisation.

Please Note: Magnet included

www.pyronix.com

RS2-WE



Adaptable, optimised & stylish

- **Fit as required with magnetic contact & roller shutter**

Consisting of both, the RS2-WE provides flexibility to the installation. The roller shutter connects directly to the window or door to report an unauthorised opening or tamper.

Expand the system with two universal inputs

Through the RS2-WE, two independent universal inputs can be utilised to add any other device that the installation requires.

Faster installation, less invasion, upsell opportunities & the same superior security with two-way wireless technology

- **No wires, no fuss**



As the system is fully wireless there is no need to run wiring by lifting floorboards or moving furniture, saving you time and money.

- **One-Push-To-Learn**

A feature in all Enforcer wireless devices that means learning them onto the system can be done in seconds. A simple one button learning feature for easy installation.

- **Signal Strength Indicators (SSI)**

SSI in all Enforcer wireless devices allow them to be optimally positioned during installation, without the need to refer back to the panel.

Partcode	RS2-WE
Inputs	
Magnetic contact plug and play	×
Shock sensor and magnetic contact / universal transmitter with 2 wireless channels	×
Magnetic contact and one channel universal transmitter	×
Magnetic contact and Roller shutter support / 2 channel universal transmitter	✓
Key Features	
Terminal for N/C input and reed switch	✓
Tamper input	✓
Front and rear tamper protection	✓
Signal Strength Indicators (SSI)	✓
Magnet included	✓
Electrical Specifications	
Transmission frequency	868MHz, FM transceiver
Transmission method	128bit encrypted radio protocol
Range in open space	1600m
3V lithium battery included	1 x CR2
Minimum battery life (years)	2
Warranty	2 years
Certifications	
Electrical conformity	CE
EN50131	Grade 2
Environmental class	II
	Self-certified
	Self-certified

- **Self-aware sensors**

The sensor will tell the control panel when it has low battery, is in fault, or has failed supervision. The sensors provide the information the control panel needs to ensure it stays safe and secure.

Beat the burglar with tamper protection

This ensures that maximum security is maintained against accidental or malicious tampering of the system, providing that added peace of mind that the system is secure.

Meet the required security standard with Grading options

The RS2-WE is Grade 2 for the superior security the installation needs.