

DHI-VTO2111D-WP

1MP Wi-Fi Villa Outdoor Station



Technical Specification	
Mode	DHI-VTO2111D-WP
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/4" 1MP CMOS
Lens	2.2mm
Angle of View	D:125° H:105°
Day/Night	ICR
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Operation Mode	

Features

- HD CMOS camera
- · Large field of view angle
- · Night vision
- · Voice indication
- \cdot Remote intercom with mobile APP
- · Surface mounted













Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP

General

Ingress Protection	IP65
Tamper Switch	1
Memory Slot	Micro SD, Max 32G
Installation	Surface
Material	Plastic
Power	DC 12V,PoE(802.3af)
Power Consumption	Standby ≤1W, Work ≤10W
Working Environments	-30°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	135mm×70.4mm×34.4mm
Weight	0.4Kg

IEEE802.11b/g

Single Mechanical Button

 $2(1\,\mbox{relay}$ out for main lock, 1 extended by access control module)

www.dahuasecurity.com

2(1ch unlock button, 1ch feedback)

Mifare Card

1m

Keypad

Reader


Body Approaching
Interface


Door Control


Alarm In RS485

Network _{Wi-Fi}

Dimensions







Application

1 – Smart Doorbell

Call Mobile phone APP directly without indoor monitor



2 – Video Intercom

- Color video & audio call
- IPC surveillance
- Alarm integration
- Remote intercom with mobile APP

